

IDEAL LOGIC+ 30 BOILER INTERNAL

MANUFACTURED BY:

ideal
HEATING

The Logic+ 30 **Condensing** System Boiler provides excellent energy saving, and performs quietly in your home.

- Made in the UK
- 1:5 Modulation rate
- Built in Frost Protection
- Large backlit LCD display
- Aluminium Silicon Heat Exchanger
- Light weight and compact design
- Quiet operation
- User friendly control panel



10 YEAR*
WARRANTY



MODELS

Logic+ 30kW System

MEASUREMENTS

700 (H) x 395 (W) x 278 (D) mm

MAGNACLEAN FILTER



WATER TREATMENT



MELBOURNE

Head Office & Showroom
11 Fiveways Blvd
Keysborough VIC 3173
P: 1300 001 800

SYDNEY

Showroom & Warehouse
Unit G7, Alexandria Industrial Estate
35-39 Bourke Road, Alexandria NSW 2015
P: 02 7209 6235



enquiries@huntheat.com.au



huntheat.com.au

General Data		30 System		
Gas Supply - NG/LPG		1.13kPa / 2.75kPa		
Gas Supply Connection		1/2"		
Flow Connection		3/4"		
Return Connection		3/4"		
Flue Terminal Diameter		mm	100	
CO2 Content (± 0.7) NG/LPG	Max. CH	8.9%/10.7%		
	Min. CH	8.7%/10.4%		
Maximum Working Pressure (Sealed Systems)		kPa	250	
Electrical Supply		230 V ~ 50 Hz		
Power Consumption		W	100	
Min. thermostat cable size		1mm twin active		
Water Content		Litre	1.2	
Height		mm	700	
Width		mm	395	
Depth		mm	278	
Packaged Weight		kg	31.5	
Installation Weight		kg	26.1	
Performance Data		Min	Max	
Boiler output - Mean 70°C		kW	6.1	30.3
Boiler output - Mean 40°C		kW	6.4	31.0
Gas Consumption		MJ/h	23.01	119.41
Boiler Efficiency		%	91.1	

