INTEC V2 INTERNAL BOILERS

MANUFACTURED BY:

IMMERGAS

- Stainless steel condensing heat exchanger
- 1:5 modulation rate
- Grundfos 6/7m modulating pump
- Intelligent management interface with simple to use controls
- FREE upgrade to 5 year warranty if you purchase a Premier Pack
- H_2 ready

HUNT HEATING®

5 YEAR* WARRANTY

ADEY PROFESSIONAL 2 FILTER

ADEY CHEMICALS

IAPMO OCEANA™

MODELS
Intec V2 20kW System
Intec V2 30kW System

MEASUREMENTS
712 (H) x 440 (W) x 260 (D) mm

MELBOURNE
Head Office & Showroom
11 Fiveways Blvd
Keysborough VIC 3173
P: 1300 001 800

SYDNEY
Showroom & Warehouse
Unit G7, Alexandria Industrial Estate
35-39 Bourke Road, Alexandria NSW 2015
P: 02 7209 6235

enquiries@huntheat.com.au

www. huntheat.com.au

		Intec 20 System	Intec 30 System
Nominal gas consumption	MJ/h	80.2	117.4
Turndown gas consumption	MJ/h	18	24
Nominal heat output (useful)	kW	19.6	28.7
Minimum heat output (useful)	kW	4.3	5.8
Efficiency 80/60 Nom./Min.	%	97.8/96.6	97.8/96.9
Efficiency 50/30 Nom./Min.	%	106.5/107.6	106.3/107.6
Efficiency 40/30 Nom./Min.	%	108.0/108.4	107.2/108.6
Casing losses with burner On/Off (80-60°C)	W	20 / 88	29 / 88
Working pressure (min/max)	kPa	50/300	
Central heating circuit max. operating temperature	°C	90	
Adjustable central heating temperature	°C	20-85	
System expansion vessel total volume	l	10	
Expansion vessel factory-set pressure	bar	1	
Water content in boiler	l	3.3	3.4
Available head ar 1000 l/h flow rate	kPa	24.4	30.4
Weight of full boiler	kg	34.5	36.8
Weight of empty boiler	kg	31.2	33.4
Electrical connection	V/Hz	230/50	
Nominal power absorption	A	0.7	0.9
Electrical protection index		IPX5D	
Standard frost protection	°C	-5	



Key:

G - Gas supply
F - System flow
R - System return
MU - Storage tank unit flow
RU - Storage tank unit return
SC - Condensate drain

HUNT HEATING®

* Please contact Hunt Heating for terms & conditions.